

Sito Palo Bollard Light

Description –

LED bollard for exterior with spherical head (adjustable up to 45° to the left and right) and single-sided light output (45°). Available either with spherical glass (Sito) or flat glass (Sito R) with internal lens, the lighting effect can be decided upon purchase.

The luminaire complies with protection class IP65 and is thus dust-tight and jet-proof. Thanks to the optional ground anchoring, it can be also mounted on loose ground. Connection to 230 V (AC) mains voltage; dimmable via trailing edge phase-cut dimmer*.

General –

Manufacture:	Occhio
Designer:	Axel Meise
Material:	Aluminium
Finish:	Matt Black / Gloss White / Matt White
Base Width:	131mm Ø
Base Depth:	14mm
Width:	130mm Ø
Height:	650mm
Depth:	119mm
Weight:	3,2Kg
Movability head:	45°

Electrical Spec –

Mounting:	Floor
Lamp:	LED
Degree:	Please see next page
Wattage:	18W
Lumens:	Please see next page
Kelvin:	2700K / 3000K
CRI:	97
Transformer:	Integral
Voltage:	230V
Dimming:	Trailing Edge
IP Rating:	IP65


Other –

Family:




C80 Contour—

Use:	Scattered light with contour beam angle (approx. 80°)
inserts:	Spherical glass Small lens high
Beam Degree:	80°
Output:	1100lm



S80 Soft—

Use:	Scattered light with soft contour beam angle (approx. 80°)
inserts:	Spherical glass Small lens high Soft edge glass
Beam Degree:	80°
Output:	980lm



S40 Soft—

Use:	Scattered light with soft contour beam angle (approx. 40°)
inserts:	Spherical glass Small lens high Fresnel lens
Beam Degree:	40°
Output:	870lm